


Light Tube Ø 30 Indirect 1500 mm Dali Version

■ 03.8112.14.DA - Black

Diffused LED light module to be installed in The Infra-Structure.




Main specifications

Number of heads	1	Net lumen (lm)	1984
Lamp category	LED	Mountings	Track
Power (W)	38W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Indirect
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	93
Beam angle C90-270 (°)	99



Beam Angle:	99°		
h(m)	E(lx)	D(m)	
1	849	2.12	
2	212	4.25	
3	94	6.37	
4	53	8.50	
5	34	10.62	

Luminous flux luminaire
1984 lm

Electrical

Voltage (V)	48.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable DALI 1		
Emergency	Without		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	1.2
Length (mm)	1544

Note

System turning fastening elements 0°-90° with a magnetic connection and mechanic security bock for a transversally installation between two lines of the profile. The Light Tube are only fed by one od the ends and do not communicate current through the other end. For wireless lighting control, choose integrated Casambi versions.

