



## Micro Battery Fixed

■ 04.6333.08B - Mercury

Recessed luminaire with LED light source. Power supply not included.




### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 611                 |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 9.2W  | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 17        |
| Beam angle C90-270 (°) | 18        |



Beam Angle: 17°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 2349  | 0.31 |
| 2    | 587   | 0.61 |
| 3    | 261   | 0.92 |
| 4    | 147   | 1.23 |
| 5    | 94    | 1.54 |

Luminous flux luminaire  
611 lm (EXTREME CUT OFF)

### Electrical

|                |                                                                                                     |                  |         |
|----------------|-----------------------------------------------------------------------------------------------------|------------------|---------|
| Frequency (Hz) | 50/60                                                                                               | Emergency        | Without |
| Voltage (V)    | 18.40                                                                                               | Insulation class | III     |
| Dimmable       | Yes                                                                                                 |                  |         |
| Driver         | Remote excluded                                                                                     |                  |         |
| Driver type    | Non Dimmable, Dimmable DALI 2, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming |                  |         |

### Physical

|                     |         |
|---------------------|---------|
| Color               | Mercury |
| Orientation         | Fixed   |
| Recessed depth (mm) | 100     |
| Weight (kg)         | 0.36    |

## Micro Battery Fixed



Continuous current power supply, 1-10V, regulable Mains, leading & trailing edge 220/240V – 50/60Hz, 500mA – 10W 60.9411



Continuous current power supply of 12-20W, 110/240V – 50/60Hz with power current selected through adjustable 350mA – 17W / 400mA – 19W / 450 / 550 / 600 / 700mA – 20W regulable Dali 1 y Dali 2 60.9222



Non dimmable continuous current power supply of 220/240V – 50/60Hz with power current selected through adjustable with switch 200 mA – 8,5W / 300 mA – 13W / 350 mA – 15W / 400 mA – 17,5W / 450 mA – 19,5W / 500 mA – 22W 60.9160



Continuous current power supply of 10-20W, 110/240V – 50/60Hz with power current selected through adjustable 250 mA – 10W / 350 mA – 15W / 400 mA – 17W / 450 mA – 19W / 500/550/600/700 mA – 20W, Dali 1 switch. 60.8847



Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W 60.9207



Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming 60.9188