



Micro Spot

New

03.2222.40A - White


Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	231
Power (W)	3W	Mountings	Track
System power (W)	3	Environment	Indoor dry location
CCT (K)	4000K		

Optical


Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	28
Beam angle C90-270 (°)	28
UGRL	12
Efficiency (lm/W)	77



Beam Angle: 28°

h(m)	E(lx)	D(m)
1	865	0.51
2	216	1.02
3	96	1.54
4	54	2.05
5	35	2.56

Luminous flux luminaire
231 lm




Electrical

Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Electronic 12V, Dimmable		
	Casambi, Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

Physical

Color	White	Spot diameter (mm)	24
Orientation	Adjustable	Length (mm)	41
Weight (kg)	0.03		
Tilt (°)	90		
Rotation (°)	267		



Micro Spot



Honeycomb
08.0190.14