

Micro Spot

New

03.2226.40A - White

Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Main specifications

Number of heads	1	**CRI**	90
Lamp category	LED	**Net lumen (lm)**	189
Power (W)	3W	**Mountings**	Track
System power (W)	3	**Environment**	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	31
Beam angle C90-270 (°)	31
UGRL	17
Efficiency (lm/W)	63



Luminous flux luminaire
189 lm

Beam Angle: 31°

h(m)	E(lx)	D(m)
1	558	0.54
2	139	1.09
3	62	1.63
4	35	2.17
5	22	2.72

Electrical

Voltage (V)	24	**Insulation class**	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Electronic 12V, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

Physical

Color	White	**Spot diameter (mm)**	24
Orientation	Adjustable	**Length (mm)**	41
Weight (kg)	0.03		
Tilt (°)	90		
Rotation (°)	267		

Micro Spot

Honeycomb
08.0190.14