



Micro Spot

New

03.2300.14A - Black


Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	216
Power (W)	3W	Mountings	Track
System power (W)	3	Environment	Indoor dry location
CCT (K)	2700K		

Optical


Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16
Beam angle C90-270 (°)	16
UGRL	11
Efficiency (lm/W)	72



Beam Angle: 16°

h(m)	E(lx)	D(m)
1	2028	0.27
2	507	0.54
3	225	0.82
4	127	1.09
5	81	1.36

Luminous flux luminaire
216 lm



Electrical

Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		

Driver type	Electronic 12V, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1 Without
-------------	--

Emergency

Physical

Color	Black	Spot diameter (mm)	24
Orientation	Adjustable	Length (mm)	41
Weight (kg)	0.03		
Tilt (°)	90		
Rotation (°)	267		

Note

Honeycomb accessory available. Must be ordered separately.

Micro Spot



Honeycomb
08.0190.14