



New

03.2301.14A - Black


Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	224
Power (W)	3W	Mountings	Track
System power (W)	3	Environment	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16
Beam angle C90-270 (°)	16
UGRL	11
Efficiency (lm/W)	74.67



Beam Angle: 16°

h(m) E(lx) D(m)

1 2103 0.27

2 526 0.54

3 234 0.82

4 131 1.09

5 84 1.36

Luminous flux luminaire
224 lm

Electrical


Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Electronic 12V, Dimmable		
	Casambi, Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

Physical

Color	Black	Spot diameter (mm)	24
Orientation	Adjustable	Length (mm)	41
Weight (kg)	0.03		
Tilt (°)	90		
Rotation (°)	267		

Note

Honeycomb accessory available. Must be ordered separately.



Micro Spot



Honeycomb
08.0190.14