


Mini Box


07.9006.01B - Matt white

Semi-recessed signalling lamp for indoor or outdoor use. 100-240V, 50-60Hz non-regulable power supply included.

Semi-recessed signalling lamp for indoor or outdoor use. 100-240V, 50-60Hz non-regulable power supply included.



Certification / Marking




Main specifications

Lamp category	LED	Environment	Indoor, Outdoor
Power (W)	1.6W		
CCT (K)	3000K		
Net lumen (lm)	73		
Mountings	Wall recessed		

Optical

Lighting type	Indirect, Direct
LED type	Power LED
Light distribution	Asymmetric
Optical type	Spot
Beam angle (°)	52
Beam angle C90-270 (°)	82



Luminous flux luminaire
73 lm

Beam Angle: 82°

h(m)	E(lx)	D(m)
1	27	2.22
2	7	4.44
3	3	6.66
4	2	8.89
5	1	11.11


Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	No		
Driver	Integrated		
Driver type	Electronic		
Emergency	Without		

Physical

Color	Matt white
Orientation	Fixed
Recessed depth (mm)	85
Weight (kg)	0.36

Mini Box

		
Junction box 08.8012.00	Flush wall Installation 08.8246.00	High density polystyrene (87x85x87mm) 80.1332