

Mini Box

■ 07.9006.01C - Matt White

Semi-recessed signalling lamp for indoor or outdoor use. 100-240V, 50-60Hz non-regulable power supply included.




Main specifications

Lamp category	LED	Mountings	Wall recessed
Power (W)	1.6W	Environment	Indoor dry location, Outdoor wet location
CCT (K)	3000K		
CRI	80		
Net lumen (lm)	69		

Optical


Lighting type	Indirect, Direct
LED type	Power LED
Light distribution	Asymmetric
Optical type	Wide flood
Beam angle (°)	59
Beam angle C90-270 (°)	89



Beam Angle: 59°

h(m)	E(lx)	D(m)
1	12	2.67
2	3	5.35
3	1	8.02
4	1	10.69
5	0	13.36

Luminous flux luminaire
69 lm



Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	3	Insulation class	II
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

Physical

Color	Matt White
Orientation	Fixed
Recessed depth (mm)	85
Weight (kg)	0.36
Length (mm)	100



Mini Box

		
Junction box 08.8012.00	High density polystyrene (87x85x87mm) 80.1332	Flush wall Installation 08.8246.00