

Mini Box

07.9006.18B - Dark Brown

Semi-recessed signalling lamp for indoor or outdoor use. 100-240V, 50-60Hz non-regulable power supply included.


Semi-recessed signalling lamp for indoor or outdoor use. 100-240V, 50-60Hz non-regulable power supply included.

Main specifications

Lamp category	LED	Mountings	Wall recessed
Power (W)	1.6W	Environment	Indoor, Outdoor
CCT (K)	3000K		
CRI	80		
Net lumen (lm)	73		

Optical

Lighting type	Indirect, Direct
LED type	Power LED
Light distribution	Asymmetric
Optical type	Spot
Beam angle (°)	52
Beam angle C90-270 (°)	82



Beam Angle: 82°

h(m)	E(lx)	D(m)
1	27	2.22
2	7	4.44
3	3	6.66
4	2	8.89
5	1	11.11


Luminous flux luminaire
73 lm

Electrical


Frequency (Hz)	50/60	Insulation class	II
Dimmable	No		
Driver	Integrated		
Driver type	Electronic		
Emergency	Without		

Physical

Color	Dark Brown
Orientation	Fixed
Recessed depth (mm)	85
Weight (kg)	0.36



Certification / Marking



Mini Box

		
<p>Junction box 08.8012.00</p>	<p>Flush wall Installation 08.8246.00</p>	<p>High density polystyrene (87x85x87mm) 80.1332</p>