





Mini Box

■ 07.9006.72C - Grey

Semi-recessed signalling lamp for indoor or outdoor use. 100-240V, 50-60Hz non-regulable power supply included.


Main specifications

Lamp category	LED	Mountings	Wall recessed
Power (W)	1.6W	Environment	Indoor dry location, Outdoor wet location
CCT (K)	3000K		
CRI	80		
Net lumen (lm)	51		



Optical

Lighting type	Indirect, Direct
LED type	Power LED
Light distribution	Asymmetric
Optical type	Wide flood
Beam angle (°)	54
Beam angle C90-270 (°)	88



Luminous flux luminaire
51 lm

Beam Angle:	54°	
h(m)	E(lx)	D(m)
1	4	2.69
2	1	5.38
3	0	8.06
4	0	10.75
5	0	13.44


Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	3	Insulation class	II
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

Physical

Color	Grey
Orientation	Fixed
Recessed depth (mm)	85
Weight (kg)	0.36
Length (mm)	100

Mini Box



High density polystyrene
(87x85x87mm)
80.1332

Flush wall Installation
08.8246.00

Junction box
08.8012.00