

Minikelvin Wall Flex

■ F4185030 - Black

Diffuse illumination lighting device for wall mounting Wall attachment in die-cast aluminium. The adaptor is on the plug and the useful cable length is 200 cm. ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).


Diffuse illumination lighting device for wall mounting Wall attachment in die-cast aluminium. The adaptor is on the plug and the useful cable length is 200 cm. ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).

Main specifications

Number of heads	1	Net lumen (lm)	96
Lamp category	LED	Mountings	Wall surface
Power (W)	4W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	85		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	111



Beam Angle: 111°

h(m)	E(lx)	D(m)
1	36	2.89
2	9	5.77
3	4	8.66
4	2	11.55
5	1	14.44

Luminous flux luminaire
96 lm

Electrical

Dimmable	Yes
Driver	Remote included
Driver type	Dimmable
Emergency	Without
Insulation class	III

Physical

Color	Black
Orientation	Adjustable
Weight (kg)	0.38

