


## Minikelvin Wall Flex

**F4185057 - Chrome**

Diffuse illumination lighting device for wall mounting Wall attachment in die-cast aluminium. The adaptor is on the plug and the useful cable length is 200 cm. ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).

Diffuse illumination lighting device for wall mounting Wall attachment in die-cast aluminium. The adaptor is on the plug and the useful cable length is 200 cm. ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	96
<b>Lamp category</b>	LED	<b>Mountings</b>	Wall surface
<b>Power (W)</b>	4W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	85		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wide flood
<b>Beam angle (°)</b>	111



<b>Beam Angle: 111°</b>		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	36	2.89
2	9	5.77
3	4	8.66
4	2	11.55
5	1	14.44

Luminous flux luminaire  
96 lm

### Electrical

<b>Dimmable</b>	Yes
<b>Driver</b>	Remote included
<b>Driver type</b>	Dimmable
<b>Emergency</b>	Without
<b>Insulation class</b>	III

### Physical

<b>Color</b>	Chrome
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	0.38

