



Moonline Light Stripe 500 mm

06.1142.00B - White


LED lighting module for scattered light, to be installed in Moonline system. PMMA diffuser guarantees uniform lighting. For easy removal order accessory 08.8915.00

Main specifications

Number of heads	1	CRI	80
Lamp category	LED	Net lumen (lm)	274
Power (W)	8W	Mountings	Track
System power (W)	10W	Environment	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Asymmetric
Optical type	Diffused light
Beam angle (°)	82
Beam angle C90-270 (°)	125



Beam Angle: 81°

h(m) E(lx) D(m)

1 119 1.72


2 30 3.44

3 13 5.16

4 7 6.88

5 5 8.60

Luminous flux luminaire
274 lm (EXTREME CUT OFF)



Electrical


Voltage (V)	24	Insulation class	III
Dimmable	No		
Driver	Remote excluded		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	White
Orientation	Fixed
Weight (kg)	0.31
Length (mm)	500

Note

Moonline is an electric system supplied at 24V and limited to a maximum current of 10A. To avoid overload problems, the installation of an independent 240W power supply source is recommended for every 12 m installed.



Moonline Light Stripe 500 mm



Accessory to remove the Light Strip
modules much more easy
08.8915.00