



New

03.6306.14.CB - Black


Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Main specifications

Lamp category	LED	Net lumen (lm)	674
Power (W)	10W	Mountings	Track
System power (W)	11.3	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	11
Beam angle C90-270 (°)	11
UGRL	3
Efficiency (lm/W)	59.65



Beam Angle: 11°

h(m) E(lx) D(m)

1 12572 0.20

2 3143 0.40

3 1397 0.60

4 786 0.80

5 503 1.00

Luminous flux luminaire
674 lm (EXTREME CUT OFF)

Electrical



Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		
Emergency	Without		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	0.35
Length (mm)	160
Lifespan (L70 B10)	L80B50

Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.



Multi Spot 4 Casambi integrated



Frosted Flood lens
08.8761.00



Elliptical Lens
08.8759.00



Frosted Medium lens
08.8760.00