


Multi Spot 4 Dali Version

■ 03.6305.14.DA - Black

Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.




Main specifications

Lamp category	LED	Mountings	Track
Power (W)	10W	Environment	Indoor
CCT (K)	2700K		
CRI	90		
Net lumen (lm)	630		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	11
Beam angle C90-270 (°)	11



Beam Angle:	11°	
h(m)	E(lx)	D(m)
1	11747	0.20
2	2937	0.40
3	1305	0.60
4	734	0.80
5	470	1.00

Luminous flux luminaire
630 lm

Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic		
Emergency	Without		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	0.35
Length (mm)	160

Note

For wireless lighting control, choose integrated Casambi versions. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.



Multi Spot 4 Dali Version



Frosted Medium lens
08.8760.00



Frosted Flood lens
08.8761.00



Elliptical Lens
08.8759.00