





### **3.6305.14** - Black

 $\label{thm:local_problem} Accent lighting \ LED \ module \ to \ be \ installed \ in \ The \ Running \ Magnet \ System. \ Built-in \ DC/DC \ electronic \ voltage \ converter.$ 

## Main specifications


Lamp category	LED
Power (W)	10W
System power (W)	11.3
CCT (K)	2700K
CRI	90

Net lumen (lm) 630 Mountings Track

**Environment** Indoor dry location

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	11
Beam angle C90-270 (°)	11
UGRL	3
Efficiency (lm/W)	55.75



Beam Angle: 11° D(m) h(m) = E(Ix)11747 0.20 2937 0.40 3 1305 0.60 4 0.80 734 5 470 1.00

Luminous 630 lm

_	00tr100
_	lectrical
_	

Voltage (V)	24.00
Dimmable	Yes
Driver	Remote
	excluded
Driver type	Dimmer on
	board
Emergency	Without

Insulation class

Physical

Color	Black
Orientation	Fixed
Weight (kg)	0.35
Length (mm)	160
Lifespan (L70 B10)	L80B50



160

ø34

#### Note

For wireless lighting control, choose integrated Casambi versions. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.

# Multi Spot 4 On Board Dimmer







Elliptical Lens 08.8759.00 Frosted Medium lens 08.8760.00

Frosted Flood lens 08.8761.00