





■ 03.6306.14 - Black

Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Main specifications


Lamp category	LED
Power (W)	10W
System power (W)	11.3
CCT (K)	3000K
CRI	90

Net lumen (lm) 674 Mountings Track

Environment Indoor dry location

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	11
Beam angle C90-270 (°)	11
UGRL	3
Efficiency (lm/W)	59.65



Beam Angle: 11° h(m) = E(Ix)D(m) 12572 0.20 3143 0.40 3 1397 0.60 4 786 0.80 5 503 1.00

Luminous	tlux	luminai
674 lm		

ø34

Voltage (V)	24.00
Dimmable	Yes
Driver	Remote
	excluded
Driver type	Dimmer o
	board
Emergency	Without

Insulation class

Ш

-					
∇	IP 20	EAE	CE	RETILAP	GWT 850°

160

Physical

Electrical

Color	Black
Orientation	Fixed
Weight (kg)	0.35
Length (mm)	160
Lifespan (L70 B10)	L80B50

Note

For wireless lighting control, choose integrated Casambi versions. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.

Multi Spot 4 On Board Dimmer







Elliptical Lens 08.8759.00 Frosted Medium lens 08.8760.00

Frosted Flood lens 08.8761.00