

Nano Spot

New

03.2215.14A - Black

Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Main specifications

Number of heads	1	**CRI**	90
Lamp category	LED	**Net lumen (lm)**	77
Power (W)	2W	**Mountings**	Track
System power (W)	1.6	**Environment**	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	32
Beam angle C90-270 (°)	32
UGRL	17
Efficiency (lm/W)	48.13



Luminous flux luminaire
77 lm

Beam Angle: 32°

h(m)	E(lx)	D(m)
1	238	0.57
2	60	1.15
3	26	1.72
4	15	2.29
5	10	2.87

Electrical

Voltage (V)	24	**Insulation class**	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Electronic 12V, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

Physical

Color	Black	**Spot diameter (mm)**	13
Orientation	Adjustable	**Length (mm)**	41
Weight (kg)	0.02		
Tilt (°)	90		
Rotation (°)	267		