



Nano Spot

New

■ 03.2217.14A - Black

Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.




Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	86
Power (W)	2W	Mountings	Track
System power (W)	1.6	Environment	Indoor dry location
CCT (K)	4000K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	31
Beam angle C90-270 (°)	32
UGRL	16
Efficiency (lm/W)	53.75



Beam Angle: 31°

h(m)	E(lx)	D(m)
1	266	0.57
2	66	1.15
3	30	1.72
4	17	2.29
5	11	2.87

Luminous flux luminaire
86 lm

Electrical

Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Electronic 12V, Dimmable		
	Casambi, Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

Physical

Color	Black	Spot diameter (mm)	13
Orientation	Adjustable	Length (mm)	41
Weight (kg)	0.02		
Tilt (°)	90		
Rotation (°)	267		