
Neutron I Fixed Round Ceiling

07.9502.04B - Black

LED downlight. Phosphor LED module integrated. Remote electronic driver 220/240V included. Watertight connection device included.








Main specifications

Number of heads	1	**Net lumen (lm)**	869
Lamp category	LED	**Mountings**	Ceiling recessed
Power	8.2W	**Environment**	Indoor, Outdoor
CCT	3000K		
CRI	80		

Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	38
Beam angle C90-270 (°)	38



Luminous flux luminaire
869 lm

Beam Angle: 38°

h(m)	E(lx)	D(m)
1	2089	0.69
2	522	1.38
3	232	2.07
4	131	2.77
5	84	3.46

MEDIUM

Electrical

Frequency (Hz)	50/60	**Emergency**	With
Lamp holder	LED	**Insulation class**	II
Dimmable	No		
Driver	Remote		
Driver type	Electronic		

Physical

Color	Black
Orientation	Fixed
Trim	yes
Recessed depth (mm)	120
Weight (kg)	1.20

Certification / Marking

IP 67 RETILAP

Neutron I Fixed Round Ceiling



Junction box
08.8012.00