

Pure 1 Spot Ceiling

■ 09.2455.02A - Grey

Spotlight to be installed on ceiling/wall with LED light source. 220/240V, 50/60Hz power supply integrated.




Main specifications

Number of heads	1	Net lumen (lm)	1058
Lamp category	LED	Mountings	Ceiling surface
Power (W)	15.7W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	80		

Optical


Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	15
Beam angle C90-270 (°)	15



Beam Angle: 15°

h(m)	E(lx)	D(m)
1	12736	0.26
2	3184	0.52
3	1415	0.78
4	796	1.04
5	509	1.29

Luminous flux luminaire
1058 lm




Electrical

Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without
Insulation class	I

Physical


Color	Grey
Orientation	Adjustable
Weight (kg)	1.20
Tilt (°)	90
Rotation (°)	180



Pure 1 Spot Ceiling



Pure 1 Pro external ring accessory
08.8232.14



Daylight filter
08.8160.DL




Honeycomb
08.8169.14



Holding ring
08.8166.14



Flood lens
08.8175.68



Cold light filter
08.8160.CL



Pure 1 Pro external ring accessory
08.8232.30




U.V. filter
08.8160.98.OD




Elliptical lens
08.8163.68




Pure 1 Pro external ring accessory
08.8232.02




Neodimium
08.8160.ND




Amber filter
08.8160.66.OD



Blue filter
08.8160.64.OD



Red filter
08.8160.67.OD



Sky blue filter
08.8160.65.OD



Hot Light
08.8160.69



I.R. filter
08.8160.68