

## Pure 1 Spot Ceiling

09.2455.30B - White

Spotlight to be installed on ceiling/wall with LED light source. 220/240V, 50/60Hz power supply integrated.




## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1510                |
| Lamp category   | LED   | Mountings      | Ceiling surface     |
| Power (W)       | 15.7W | Environment    | Indoor dry location |
| CCT (K)         | 2700K |                |                     |
| CRI             | 80    |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 15        |
| Beam angle C90-270 (°) | 15        |



Beam Angle: 15°

|   | h(m)  | E(lx) | D(m) |
|---|-------|-------|------|
| 1 | 14674 | 0.26  |      |
| 2 | 3668  | 0.52  |      |
| 3 | 1630  | 0.78  |      |
| 4 | 917   | 1.04  |      |
| 5 | 587   | 1.30  |      |

Luminous flux luminaire  
1510 lm (EXTREME CUT OFF)

## Electrical

|                |              |                  |   |
|----------------|--------------|------------------|---|
| Frequency (Hz) | 50/60        | Insulation class | I |
| Dimmable       | No           |                  |   |
| Driver         | Integrated   |                  |   |
| Driver type    | Non Dimmable |                  |   |
| Emergency      | Without      |                  |   |

## Physical

|              |            |
|--------------|------------|
| Color        | White      |
| Orientation  | Adjustable |
| Weight (kg)  | 1.20       |
| Tilt (°)     | 90         |
| Rotation (°) | 180        |

