

## Pure 1 Spot Ceiling

■ 09.2457.30A - White

Spotlight to be installed on ceiling/wall with LED light source. 220/240V, 50/60Hz power supply integrated.




## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 956                 |
| Lamp category   | LED   | Mountings      | Ceiling surface     |
| Power (W)       | 15.7W | Environment    | Indoor dry location |
| CCT (K)         | 2700K |                |                     |
| CRI             | 80    |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 37        |
| Beam angle C90-270 (°) | 37        |



Beam Angle: 37°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 2215  | 0.67 |
| 2    | 554   | 1.34 |
| 3    | 246   | 2.02 |
| 4    | 138   | 2.69 |
| 5    | 89    | 3.36 |



Luminous flux luminaire  
956 lm

## Electrical

|                |              |                  |   |
|----------------|--------------|------------------|---|
| Frequency (Hz) | 50/60        | Insulation class | I |
| Dimmable       | No           |                  |   |
| Driver         | Integrated   |                  |   |
| Driver type    | Non Dimmable |                  |   |
| Emergency      | Without      |                  |   |

## Physical


|              |            |
|--------------|------------|
| Color        | White      |
| Orientation  | Adjustable |
| Weight (kg)  | 1.20       |
| Tilt (°)     | 90         |
| Rotation (°) | 180        |




Pure 1 Spot Ceiling



Hot Light  
08.8160.69



Amber filter  
08.8160.66.OD



Daylight filter  
08.8160.DL



Pure 1 Pro external ring accessory  
08.8232.02




Honeycomb  
08.8169.14




Pure 1 Pro external ring accessory  
08.8232.30




Elliptical lens  
08.8163.68



Red filter  
08.8160.67.OD




Blue filter  
08.8160.64.OD




---

Neodimium  
08.8160.ND



---

I.R. filter  
08.8160.68




---

Sky blue filter  
08.8160.65.OD



---

Pure 1 Pro external ring accessory  
08.8232.14



---

Cold light filter  
08.8160.CL



---

Flood lens  
08.8175.68



---

Holding ring  
08.8166.14



---

U.V. filter  
08.8160.98.OD