



Pure 1 Spot Ceiling

■ 09.2460.02C - Grey

Spotlight to be installed on ceiling/wall with LED light source. Electronic transformer 220/240V, 50/60Hz for phosphor LED integrated.

Spotlight to be installed on ceiling/wall with LED light source. Electronic transformer 220/240V, 50/60Hz for phosphor LED integrated.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 1377 |
| Lamp category | LED | Mountings | Ceiling surface |
| Power (W) | 19.5W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 80 | | |

Optical

| | |
|-------------------------------|--------------|
| Lighting type | Direct |
| LED type | Phosphor LED |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 23 |
| Beam angle C90-270 (°) | 23 |



| | | |
|------------------------|--------------|-------------|
| Beam Angle: 23° | | |
| h(m) | E(lx) | D(m) |
| 1 | 5968 | 0.41 |
| 2 | 1492 | 0.81 |
| 3 | 663 | 1.22 |
| 4 | 373 | 1.62 |
| 5 | 239 | 2.03 |



Luminous flux luminaire
1377 lm

Electrical

| | | | |
|-----------------------|--------------|-------------------------|---|
| Frequency (Hz) | 50/60 | Insulation class | I |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Non Dimmable | | |
| Emergency | Without | | |

Physical


| | |
|---------------------|------------|
| Color | Grey |
| Orientation | Adjustable |
| Weight (kg) | 1.20 |
| Tilt (°) | 90 |
| Rotation (°) | 180 |




Pure 1 Spot Ceiling




Pure 1 Pro external ring accessory
08.8232.14



Sky blue filter
08.8160.65.OD



Amber filter
08.8160.66.OD



Cold light filter
08.8160.CL



I.R. filter
08.8160.68



Flood lens
08.8175.68



Hot Light
08.8160.69




Neodimium
08.8160.ND



Honeycomb
08.8169.14




U.V. filter
08.8160.98.OD




Daylight filter
08.8160.DL



Pure 1 Pro external ring accessory
08.8232.02



Red filter
08.8160.67.OD



Blue filter
08.8160.64.OD



Pure 1 Pro external ring accessory
08.8232.30



Elliptical lens
08.8163.68



Holding ring
08.8166.14