



## Pure 1 Spot Ceiling

09.2465.30A - White


Spotlight to be installed on ceiling/wall with LED light source. 220/240V, 50/60Hz power supply integrated.

### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1139                |
| Lamp category   | LED   | Mountings      | Ceiling surface     |
| Power (W)       | 15.7W | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 80    |                |                     |

### Optical


|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 15        |
| Beam angle C90-270 (°) | 15        |



Beam Angle: 15°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 12831 | 0.27 |
| 2    | 3208  | 0.54 |
| 3    | 1426  | 0.81 |
| 4    | 802   | 1.07 |
| 5    | 513   | 1.34 |

Luminous flux luminaire  
1139 lm




### Electrical

|                |              |                  |   |
|----------------|--------------|------------------|---|
| Frequency (Hz) | 50/60        | Insulation class | I |
| Dimmable       | No           |                  |   |
| Driver         | Integrated   |                  |   |
| Driver type    | Non Dimmable |                  |   |
| Emergency      | Without      |                  |   |

### Physical

|              |            |
|--------------|------------|
| Color        | White      |
| Orientation  | Adjustable |
| Weight (kg)  | 1.20       |
| Tilt (°)     | 90         |
| Rotation (°) | 180        |



Pure 1 Spot Ceiling




Pure 1 Pro external ring accessory  
08.8232.02



Honeycomb  
08.8169.14




Hot Light  
08.8160.69



Blue filter  
08.8160.64.OD



Elliptical lens  
08.8163.68



Cold light filter  
08.8160.CL



Pure 1 Pro external ring accessory  
08.8232.30



Holding ring  
08.8166.14



Flood lens  
08.8175.68




---

I.R. filter  
08.8160.68




---

Pure 1 Pro external ring accessory  
08.8232.14




---

Daylight filter  
08.8160.DL




---

Red filter  
08.8160.67.OD




---

Neodimium  
08.8160.ND



---

Amber filter  
08.8160.66.OD



---

Sky blue filter  
08.8160.65.OD



---

U.V. filter  
08.8160.98.OD