



## Pure 1 Spot Ceiling

■ 09.2466.02A - Grey


Spotlight to be installed on ceiling/wall with LED light source. 220/240V, 50/60Hz power supply integrated.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	958
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling surface
<b>Power (W)</b>	15.7W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	80		


### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	24
<b>Beam angle C90-270 (°)</b>	24



<b>Beam Angle: 24°</b>		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	3932	0.43
2	983	0.85
3	437	1.28
4	246	1.70
5	157	2.13

Luminous flux luminaire  
958 lm




### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Electronic		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Grey
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	1.20
<b>Tilt (°)</b>	90
<b>Rotation (°)</b>	180

### Certification / Marking




## Pure 1 Spot Ceiling




---

Flood lens  
08.8175.68




---

Blue filter  
08.8160.64.OD




---

Sky blue filter  
08.8160.65.OD



---

Amber filter  
08.8160.66.OD



---

Red filter  
08.8160.67.OD



---

I.R. filter  
08.8160.68




---

Hot Light  
08.8160.69




---

U.V. filter  
08.8160.98.OD




---

Cold light filter  
08.8160.CL



---

Daylight filter  
08.8160.DL



---

Neodimium  
08.8160.ND



---

Elliptical lens  
08.8163.68



---

Holding ring  
08.8166.14



---

Honeycomb  
08.8169.14



---

Pure 1 Pro external ring accessory  
08.8232.02



---

Pure 1 Pro external ring accessory  
08.8232.14



---

Pure 1 Pro external ring accessory  
08.8232.30