

Certification / Marking

IP 20

Pure 3 Downlight

Pure 3 Downlight

Metal halide lamp recessed downlight. Remote control gear not included

Main specifications

Number of heads	1
Mountings	Ceiling recessed

Optical

Optical type	Wide flood
Beam angle (°)	44
Beam angle C90-270 (°)	44



Luminous flux luminaire
6600 lm

Beam Angle: 44°

h(m)	E(lx)	D(m)
1	7575	0.81
2	1894	1.61
3	842	2.42
4	473	3.23
5	303	4.04

WIDE FLOOD

Electrical

Frequency (Hz)	50/60
Emergency	Without

Physical

Weight (kg)	1.88

Pure 3 Downlight



Elliptical light distribution lens
08.8165.68



Blue filter
08.8162.64.OD



Sky blue filter
08.8162.65.OD



Amber filter
08.8162.66.OD



Red filter
08.8162.67.OD



U.V. filter
08.8162.98.OD



I.R. filter
08.8162.68



Hot Light
08.8162.69



Cold light filter
08.8162.CL



Daylight filter
08.8162.DL



Neodimium
08.8162.ND



Installation Frame For Trim
08.8151.30



Installation Frame For Trim Grey
08.8151.02



Installation Frame For Trim Black
08.8151.14