

Pure Downlight

■ 09.1600.02 - Grey

Recessed 12V halogen lamp luminaire. Remote transformer not included.

Main specifications

Number of heads	1
Lamp category	Halogen
Power (W)	50W Max.
Mountings	Ceiling recessed
Environment	Indoor

Optical

Lamp type	QR-CBC 51
Light distribution	Symmetric
Beam angle (°)	10

Electrical


Frequency (Hz)	50/60
Lamp holder	GX5.3
Driver	Remote
Emergency	Without
Insulation class	III

Physical

Color	Grey	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	138		
Weight (kg)	0.96		
Tilt (°)	60		

Note

Installation frame must be ordered separately.



Pure Downlight



Installation Frame For No Trim
08.8152.00




Holding ring
08.8166.14




Elliptical lens
08.8163.68




Honeycomb
08.8169.14




Blue filter
08.8160.64.OD



Sky blue filter
08.8160.65.OD



Amber filter
08.8160.66.OD



Red filter
08.8160.67.OD




I.R. filter
08.8160.68




U.V. filter
08.8160.98.OD




Hot Light
08.8160.69



Cold light filter
08.8160.CL



Daylight filter
08.8160.DL



Neodimium
08.8160.ND



Flood lens
08.8175.68



Installation Frame For Trim White
08.8149.30



Installation Frame For Trim Grey
08.8149.02



Installation Frame For Trim White
08.8149.14



Pure 1 Pro external ring accessory
08.8232.30

Pure 1 Pro external ring accessory
08.8232.02

Pure 1 Pro external ring accessory
08.8232.14