

Pure Downlight

09.1600.30 - White

Recessed 12V lamp luminaire. Remote transformer not included.

Main specifications

Number of heads	1
Lamp category	LED retrofit
Mountings	Ceiling recessed
Environment	Indoor dry location

Optical

Lamp type	QR-CBC 51
Light distribution	Symmetric
Beam angle (°)	10

Electrical


Frequency (Hz)	50/60	Insulation class	III
Lamp holder	GX5.3		
Driver	Remote excluded		
Driver type	Electronic 12V		
Emergency	Without		

Physical

Color	White
Orientation	Adjustable
Recessed depth (mm)	138
Weight (kg)	0.96
Rotation (°)	360

Note

Installation frame must be ordered separately.



Pure Downlight



Honeycomb
08.8169.14



Installation Frame For No Trim
08.8152.00



Installation Frame For Trim Black
08.8149.14



Elliptical lens
08.8163.68




Pure 1 Pro external ring accessory
08.8232.02



Holding ring
08.8166.14



Hot Light
08.8160.69




Neodimium
08.8160.ND




Installation Frame For Trim White
08.8149.30



Pure 1 Pro external ring accessory
08.8232.30




I.R. filter
08.8160.68




Cold light filter
08.8160.CL



Installation Frame For Trim Grey
08.8149.02



Amber filter
08.8160.66.OD




Blue filter
08.8160.64.OD



U.V. filter
08.8160.98.OD



Pure 1 Pro external ring accessory
08.8232.14



Daylight filter
08.8160.DL



Flood lens
08.8175.68

Red filter
08.8160.67.OD

Sky blue filter
08.8160.65.OD