


Pure Downlight

09.1631.30C - White

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.




Main specifications

Number of heads	1	Net lumen (lm)	797
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	12W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	98		

Optical

LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	46
Beam angle C90-270 (°)	46



Beam Angle: 46°

h(m)	E(lx)	D(m)
1	1418	0.84
2	355	1.69
3	158	2.53
4	89	3.37
5	57	4.21

Luminous flux luminaire
797 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

Physical


Color	White	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	138		
Weight (kg)	0.96		
Tilt (°)	60		

Note

Installation frame must be ordered separately.




Pure Downlight



I.R. filter
08.8160.68

Honeycomb
08.8169.14



Installation Frame For No Trim
08.8152.00



Cold light filter
08.8160.CL

U.V. filter
08.8160.98.OD


Installation Frame For Trim Grey
08.8149.02



Neodimium
08.8160.ND

Pure 1 Pro external ring accessory
08.8232.14

Amber filter
08.8160.66.OD




Red filter
08.8160.67.OD



Pure 1 Pro external ring accessory
08.8232.30



Flood lens
08.8175.68



Blue filter
08.8160.64.OD



Installation Frame For Trim White
08.8149.30




Hot Light
08.8160.69



Elliptical lens
08.8163.68



Holding ring
08.8166.14



Sky blue filter
08.8160.65.OD



Daylight filter
08.8160.DL

Installation Frame For Trim Black
08.8149.14

Pure 1 Pro external ring accessory
08.8232.02