



Pure Downlight

■ 09.1641.02A - Grey

Recessed luminaire with LED light source. Power supply not included




Main specifications

Number of heads	1	Net lumen (lm)	933
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	15.7W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	80		

Optical

LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	23
Beam angle C90-270 (°)	23



Beam Angle: 23°

h(m)	E(lx)	D(m)
1	4359	0.40
2	1090	0.80
3	484	1.20
4	272	1.60
5	174	2.01

Luminous flux luminaire
933 lm

Electrical

Frequency (Hz)	50/60	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Push, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming		
Emergency	Without		


Physical

Color	Grey	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	138		
Weight (kg)	0.75		
Tilt (°)	60		


Note

Installation frame must be ordered separately.

Pure Downlight



Neodimium
08.8160.ND



Daylight filter
08.8160.DL



Honeycomb
08.8169.14



Continuous current power supply of 25W, 110/240V – 50/60Hz with power current selected through adjustable 350 mA-18W / 400 mA – 21W / 500mA – 25W /600mA – 30W /700/750/900 mA – 32W switch. 1-10V or push dimming, synchronisation cables not included.
60.8533



Hot Light
08.8160.69




Pure 1 Pro external ring accessory
08.8232.14



Continuous current power supply of



Elliptical lens



Red filter

350mA – 25W / 500mA – 35W / 700mA –
 50W / 750mA – 54W / 900 / 1050 mA –
 60W switch. Dali 2, 0/1-10V or push
 dimming
 60.8530



Holding ring
 08.8166.14



Pure 1 Pro external ring accessory
 08.8232.02




Non dimmable continuous current
 power supply. 350mA – 17,5W / 500mA
 – 20W / 700mA – 20W – 220/240V –
 50/60Hz.
 60.9312




U.V. filter
 08.8160.98.OD



I.R. filter
 08.8160.68



Cold light filter
 08.8160.CL



Amber filter
 08.8160.66.OD



Installation Frame For Trim White
 08.8149.30



Installation Frame For Trim Grey
 08.8149.02




Pure 1 Pro external ring accessory
08.8232.30



Installation Frame For Trim Black
08.8149.14




Installation Frame For No Trim
08.8152.00



Blue filter
08.8160.64.OD



Continuous current power supply.
230/240V – 50/60Hz. Adjustable Current
350mA – 17W / 500mA – 24W / 700/ 750
mA – 32W switch by trailing and
leading edge dimming, mains dimming
or push dimming
60.8534



Sky blue filter
08.8160.65.OD



Flood lens
08.8175.68