


09.1642.14A - Black

Recessed luminaire with LED light source. Power supply not included

Number of heads	1	Net lumen (lm)	956
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	15.7W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	80		

LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	37
Beam angle C90-270 (°)	37



Beam Angle: 37°

h(m)	E(lx)	D(m)
1	2215	0.67
2	554	1.34
3	246	2.02
4	138	2.69
5	89	3.36


Luminous flux luminaire
956 lm

Frequency (Hz)	50/60	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Push, Dimmable 1- 10V, Dimmable DALI 1, Mains Cut Dimming		
Emergency	Without		

Color	Black	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	138		
Weight (kg)	0.75		
Tilt (°)	60		

Installation frame must be ordered separately.

Pure Downlight



Cold light filter
08.8160.CL



Installation Frame For Trim Grey
08.8149.02




Flood lens
08.8175.68




Continuous current power supply of 25W, 110/240V – 50/60Hz with power current selected through adjustable 350 mA-18W / 400 mA – 21W / 500mA – 25W /600mA – 30W /700/750/900 mA – 32W switch. 1-10V or push dimming, synchronisation cables not included.
60.8533



Continuous current power supply. 230/240V – 50/60Hz. Adjustable Current 350mA – 17W / 500mA – 24W / 700/ 750 mA – 32W switch by trailing and leading edge dimming, mains dimming or push dimming
60.8534



Amber filter
08.8160.66.OD




Blue filter




Honeycomb



Elliptical lens




Red filter
08.8160.67.OD



Hot Light
08.8160.69



Installation Frame For Trim White
08.8149.30




Daylight filter
08.8160.DL



Continuous current power supply of 25-50W, 110/240V – 50/60Hz with power current selected through adjustable 350mA – 25W /500mA – 35W/ 700mA – 50W /750mA – 54W /900/ 1050 mA – 60W switch. Dali 2, 0/1-10V or push dimming
60.8530



Pure 1 Pro external ring accessory
08.8232.14



I.R. filter
08.8160.68




Non dimmable continuous current power supply. 350mA – 17,5W / 500mA – 20W / 700mA – 20W – 220/240V – 50/60Hz.
60.8530



Pure 1 Pro external ring accessory
08.8232.02



Installation Frame For Trim Black
08.8149.14




Sky blue filter
08.8160.65.OD



Installation Frame For No Trim
08.8152.00



Pure 1 Pro external ring accessory
08.8232.30



Neodimium
08.8160.ND



U.V. filter
08.8160.98.OD



Holding ring
08.8166.14