

■ 09.1646.02A - Grey


Recessed luminaire with LED light source. Power supply not included

## Main specifications

Number of heads	1	Net lumen (lm)	958
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	15.7W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

## Optical

LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	24
Beam angle C90-270 (°)	24



Luminous flux luminaire  
958 lm

Beam Angle:	24°		
	<u>h(m)</u>	<u>E(lx)</u>	<u>D(m)</u>
1	3932	0.43	
2	983	0.85	
3	437	1.28	
4	246	1.70	
5	157	2.13	

## Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
	excluded		
<b>Driver type</b>	Dimmable Push, Dimmable 1- 10V, Dimmable DALI 1, Mains Cut Dimming		
<b>Emergency</b>	Without		

## Physical

Color	Grey	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	138		
Weight (kg)	0.75		
Tilt (°)	60		

### Note

Installation frame must be ordered separately.


Pure Downlight



Honeycomb  
08.8169.14



Installation Frame For No Trim  
08.8152.00



Daylight filter  
08.8160.DL



Continuous current power supply of  
25-50W, 110/240V - 50/60Hz with power  
current selected through adjustable  
350mA - 25W /500mA - 35W/ 700mA -  
50W /750mA - 54W /900/ 1050 mA -  
60W switch. Dali 2, 0/1-10V or push  
dimming  
60.8530




Non dimmable continuous current  
power supply. 350mA - 17,5W / 500mA  
- 20W / 700mA - 20W - 220/240V -  
50/60Hz.  
60.9312



Installation Frame For Trim White  
08.8149.30



Continuous current power supply of




Sky blue filter



I.R. filter

350 mA-18W / 400 mA – 21W / 500mA –  
25W /600mA – 30W /700/750/900 mA –  
32W switch. 1-10V or push dimming,  
synchronisation cables not included.  
60.8533



Red filter  
08.8160.67.OD




Pure 1 Pro external ring accessory  
08.8232.30



Hot Light  
08.8160.69



U.V. filter  
08.8160.98.OD



Amber filter  
08.8160.66.OD



Pure 1 Pro external ring accessory  
08.8232.02



Continuous current power supply.  
230/240V – 50/60Hz. Adjustable Current  
350mA – 17W / 500mA – 24W / 700/ 750  
mA – 32W switch by trailing and  
leading edge dimming, mains dimming



Installation Frame For Trim Grey  
08.8149.02



Elliptical lens  
08.8163.68

or push dimming  
60.8534



---

Holding ring  
08.8166.14



---

Flood lens  
08.8175.68




---

Installation Frame For Trim Black  
08.8149.14




---

Pure 1 Pro external ring accessory  
08.8232.14




---

Blue filter  
08.8160.64.OD



---

Neodimium  
08.8160.ND



---

Cold light filter  
08.8160.CL