



Pure Downlight 1-10V

■ 09.1631.14C1V - Black

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 797 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 12W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 98 | | |

Optical

| | |
|-------------------------------|--------------|
| LED type | Phosphor LED |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 46 |
| Beam angle C90-270 (°) | 46 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 46° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 1418 | 0.84 | |
| 2 | 355 | 1.69 | |
| 3 | 158 | 2.53 | |
| 4 | 89 | 3.37 | |
| 5 | 57 | 4.21 | |

Luminous flux luminaire
797 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-----------------------|-----------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable 1-10V | | |


Physical

| | | | |
|----------------------------|------------|---------------------|-----|
| Color | Black | Rotation (°) | 360 |
| Orientation | Adjustable | | |
| Recessed depth (mm) | 138 | | |
| Weight (kg) | 0.96 | | |
| Tilt (°) | 60 | | |

Note

Installation frame must be ordered separately.

Pure Downlight 1-10V




Blue filter
08.8160.64.OD



Pure 1 Pro external ring accessory
08.8232.02



Pure 1 Pro external ring accessory
08.8232.14



Cold light filter
08.8160.CL



Hot Light
08.8160.69



Elliptical lens
08.8163.68



Pure 1 Pro external ring accessory
08.8232.30



Holding ring
08.8166.14




Neodimium
08.8160.ND



Flood lens
08.8175.68



Installation Frame For Trim White
08.8149.30




Daylight filter
08.8160.DL



Installation Frame For No Trim
08.8152.00



Installation Frame For Trim Black
08.8149.14



Sky blue filter
08.8160.65.OD



Honeycomb
08.8169.14



I.R. filter
08.8160.68



Installation Frame For Trim Grey
08.8149.02



Red filter
08.8160.67.OD

Amber filter
08.8160.66.OD

U.V. filter
08.8160.98.OD