


## Pure Downlight 1-10V

■ 09.1632.14C1V - Black

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	759
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	12W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	98		

### Optical

<b>LED type</b>	Phosphor LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wide flood
<b>Beam angle (°)</b>	51
<b>Beam angle C90-270 (°)</b>	51



Beam Angle: 51°		
h(m)	E(lx)	D(m)
1	1178	0.95
2	295	1.91
3	131	2.86
4	74	3.82
5	47	4.77

Luminous flux luminaire  
759 lm (EXTREME CUT OFF)

### Electrical


<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote included		
<b>Driver type</b>	Dimmable 1-10V		

### Physical

<b>Color</b>	Black	<b>Rotation (°)</b>	360
<b>Orientation</b>	Adjustable		
<b>Recessed depth (mm)</b>	138		
<b>Weight (kg)</b>	0.96		
<b>Tilt (°)</b>	60		

### Note

Installation frame must be ordered separately.



# Pure Downlight 1-10V



---

U.V. filter  
08.8160.98.OD




---

Pure 1 Pro external ring accessory  
08.8232.30




---

Installation Frame For Trim White  
08.8149.30




---

Amber filter  
08.8160.66.OD



---

Red filter  
08.8160.67.OD



---

Daylight filter  
08.8160.DL



---

Pure 1 Pro external ring accessory  
08.8232.02




---

Pure 1 Pro external ring accessory  
08.8232.14




---

Hot Light  
08.8160.69



---

Blue filter  
08.8160.64.OD



---

Sky blue filter  
08.8160.65.OD



---

Elliptical lens  
08.8163.68



---

Flood lens  
08.8175.68



---

Honeycomb  
08.8169.14



---

Holding ring  
08.8166.14



---

I.R. filter  
08.8160.68



---

Installation Frame For Trim Black  
08.8149.14



---

Installation Frame For No Trim  
08.8152.00



---

Cold light filter  
08.8160.CL

Installation Frame For Trim Grey  
08.8149.02

Neodimium  
08.8160.ND