



Pure Spot Pro Track

■ 09.2435.14A - Black


Spotlight to be installed on 3-phase track with LED light source. 220/240V, 50/60Hz power supply integrated.

Main specifications

Number of heads	1	Net lumen (lm)	967
Lamp category	LED	Mountings	Track
Power (W)	15.7W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical


Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	14
Beam angle C90-270 (°)	14



Beam Angle: 14°

	h(m)	E(lx)	D(m)
1	12904	0.25	
2	3226	0.50	
3	1434	0.75	
4	806	1.01	
5	516	1.26	

Luminous flux luminaire
967 lm




Electrical


Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		

Physical


Color	Black
Orientation	Adjustable
Weight (kg)	1.40
Tilt (°)	90
Rotation (°)	180



Pure Spot Pro Track



Blue filter
08.8160.64.OD




Sky blue filter
08.8160.65.OD



Elliptical lens
08.8163.68



U.V. filter
08.8160.98.OD



Daylight filter
08.8160.DL



Neodimium
08.8160.ND




Honeycomb
08.8186.14




Flood lens
08.8175.68



I.R. filter
08.8160.68




Cold light filter
08.8160.CL



Red filter
08.8160.67.OD



Hot Light
08.8160.69



Amber filter
08.8160.66.OD