

## Pure Spot Pro Track

09.2580.30A - White


Spotlight to be installed on 3-phase track with LED light source. 220/240V, 50/60Hz power supply integrated.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	809
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	17.5W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	80		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	18
<b>Beam angle C90-270 (°)</b>	18



<b>Beam Angle: 18°</b>		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	6742	0.31
2	1685	0.62
3	749	0.94
4	421	1.25
5	270	1.56


Luminous flux luminaire  
809 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	1.40
<b>Tilt (°)</b>	90
<b>Rotation (°)</b>	180



## Pure Spot Pro Track



---

U.V. filter  
08.8160.98.OD



---

Honeycomb  
08.8186.14




---

Elliptical lens  
08.8163.68




---

Neodimium  
08.8160.ND




---

Cold light filter  
08.8160.CL




---

Amber filter  
08.8160.66.OD




---

Blue filter  
08.8160.64.OD



---

Sky blue filter  
08.8160.65.OD



---

Red filter  
08.8160.67.OD




---

I.R. filter  
08.8160.68



---

Hot Light  
08.8160.69



---

Daylight filter  
08.8160.DL



---

Flood lens  
08.8175.68