



Pure Spot Track

■ 09.2405.02B - Grey


Spotlight to be installed on 3-phase track with LED light source. 220/240V, 50/60Hz power supply integrated.

Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 1395 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 15.7W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 80 | | |

Optical


| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 15 |
| Beam angle C90-270 (°) | 15 |



Beam Angle: 15°

| | h(m) | E(lx) | D(m) |
|---|-------|-------|------|
| 1 | 13558 | 0.26 | |
| 2 | 3390 | 0.52 | |
| 3 | 1506 | 0.78 | |
| 4 | 847 | 1.04 | |
| 5 | 542 | 1.30 | |

Luminous flux luminaire
1395 lm (EXTREME CUT OFF)



Electrical

| | | | |
|-----------------------|--------------|-------------------------|---|
| Frequency (Hz) | 50/60 | Insulation class | I |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Non Dimmable | | |
| Emergency | Without | | |

Physical

| | |
|---------------------|------------|
| Color | Grey |
| Orientation | Adjustable |
| Weight (kg) | 1.20 |
| Tilt (°) | 90 |
| Rotation (°) | 180 |

