



Pure Spot Track

■ 09.2417.14A - Black


Spotlight to be installed on 3-phase track with LED light source. 220/240V, 50/60Hz power supply integrated.

Main specifications

| | | | |
|-----------------|-------|----------------|--------|
| Number of heads | 1 | Net lumen (lm) | 1043 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 15.7W | Environment | Indoor |
| CCT (K) | 3000K | | |
| CRI | 80 | | |


Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 37 |
| Beam angle C90-270 (°) | 37 |



| | | |
|-------------|------|------------|
| Beam Angle: | 37° | |
| | h(m) | E(lx) D(m) |
| 1 | 2454 | 0.66 |
| 2 | 614 | 1.32 |
| 3 | 273 | 1.98 |
| 4 | 153 | 2.64 |
| 5 | 98 | 3.30 |

Luminous flux luminaire
1043 lm



Electrical


| | | | |
|----------------|------------|------------------|---|
| Frequency (Hz) | 50/60 | Insulation class | I |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Electronic | | |
| Emergency | Without | | |

Physical


| | |
|--------------|------------|
| Color | Black |
| Orientation | Adjustable |
| Weight (kg) | 1.20 |
| Tilt (°) | 90 |
| Rotation (°) | 180 |




Pure Spot Track




Blue filter
08.8160.64.OD



Sky blue filter
08.8160.65.OD



Amber filter
08.8160.66.OD



Red filter
08.8160.67.OD




I.R. filter
08.8160.68




Hot Light
08.8160.69




U.V. filter
08.8160.98.OD



Cold light filter
08.8160.CL



Daylight filter
08.8160.DL



Neodimium
08.8160.ND



Elliptical lens
08.8163.68



Holding ring
08.8166.14



Honeycomb
08.8169.14



Pure 1 Pro external ring accessory
08.8232.02



Pure 1 Pro external ring accessory
08.8232.14



Pure 1 Pro external ring accessory
08.8232.30



Flood lens
08.8175.68