


Spotlight to be installed on 3-phase track with LED light source. 220/240V, 50/60Hz power supply integrated.

Number of heads	1	Net lumen (lm)	1633
Lamp category	LED	Mountings	Track
Power (W)	17.5W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	40
Beam angle C90-270 (°)	40



Beam Angle: 40°

h(m)	E(lx)	D(m)
1	3683	0.72
2	921	1.44
3	409	2.16
4	230	2.88
5	147	3.60

Frequency (Hz)	50/60
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without

Color	Black
Orientation	Adjustable
Weight (kg)	1.20
Tilt (°)	90
Rotation (°)	180

Pure Spot Track




Elliptical lens
08.8163.68



Holding ring
08.8166.14




Hot Light
08.8160.69




Red filter
08.8160.67.OD




I.R. filter
08.8160.68



Daylight filter
08.8160.DL



Sky blue filter
08.8160.65.OD



Amber filter
08.8160.66.OD



Pure 1 Pro external ring accessory
08.8232.02




U.V. filter
08.8160.98.OD




Pure 1 Pro external ring accessory
08.8232.30



Honeycomb
08.8169.14



Neodimium
08.8160.ND




Blue filter
08.8160.64.OD



Pure 1 Pro external ring accessory
08.8232.14



Flood lens
08.8175.68



Cold light filter
08.8160.CL