



### Soft Spun Halogen Large

SA.5009.1 - Raw


Recessed luminaire for halogen lamp, direct connection to mains. Electronic LED driver 220-240V / 50-60Hz integrated.

#### Main specifications

<b>Lamp category</b>	Halogen	<b>Environment</b>	Indoor dry location
<b>Power (W)</b>	161.4W + 1.4W		
<b>CRI</b>	90		
<b>Net lumen (lm)</b>	1613		
<b>Mountings</b>	Wall recessed		

#### Optical


<b>Lighting type</b>	Indirect
<b>Lamp type</b>	QT-DE-12
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light



Beam Angle DIR: 66°

h(m)	E(lx)	D(m)
1	404	3.04
2	101	6.07
3	45	9.11
4	25	12.15
5	16	15.19

Luminous flux luminaire  
2400 lm



#### Electrical

<b>Lamp holder</b>	R7S
<b>Dimmable</b>	No
<b>Driver</b>	Integrated
<b>Driver type</b>	Electronic 12V
<b>Emergency</b>	Without

#### Physical

<b>Color</b>	Raw
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	28

#### Note

QT-DE-12 diffuser / LED White base

