


## Solid Pure Ceiling/Wall Dali Version

■ 09.2865.14.DA - Black

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2355
<b>Lamp category</b>	LED	<b>Mountings</b>	Surface
<b>Power (W)</b>	23W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	4000K		
<b>CRI</b>	80		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	10
<b>Beam angle C90-270 (°)</b>	10



Beam Angle: 10°

h(m) E(lx) D(m)

1 29499 0.18

2 7375 0.35

3 3278 0.53

4 1844 0.71

5 1180 0.88


Luminous flux luminaire  
2355 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Dimmable DALI		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	1.90
<b>Rotation (°)</b>	360




## Solid Pure Ceiling/Wall Dali Version




---

Holding ring  
08.8768.14




---

Sky blue filter  
08.8766.65.OD



---

Blue filter  
08.8766.64.OD




---

Red filter  
08.8766.67.OD



---

Honeycomb anti-glare screen  
08.8763.14



---

Amber filter  
08.8766.66.OD