


## Solid Pure Ceiling/Wall Dali Version

09.2874.30.DA - White

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2486
<b>Lamp category</b>	LED	<b>Mountings</b>	Surface
<b>Power (W)</b>	30W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	22
<b>Beam angle C90-270 (°)</b>	22



Beam Angle: 22°

h(m) E(lx) D(m)

1 10807 0.39

2 2702 0.79

3 1201 1.18

4 675 1.57

5 432 1.97


Luminous flux luminaire  
2486 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Dimmable DALI		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	1.90
<b>Rotation (°)</b>	360




## Solid Pure Ceiling/Wall Dali Version




---

Amber filter  
08.8766.66.OD



---

Sky blue filter  
08.8766.65.OD




---

Blue filter  
08.8766.64.OD



---

Honeycomb anti-glare screen  
08.8763.14



---

Red filter  
08.8766.67.OD



---

Holding ring  
08.8768.14