


## Solid Pure Ceiling/Wall Dali Version

■ 09.2892.14.DA - Black

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.




### Main specifications

Lamp category	LED	Mountings	Surface
Power (W)	23W	Environment	Indoor
CCT (K)	3000K		
CRI	90		
Net lumen (lm)	1637		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	18
Beam angle C90-270 (°)	18



Beam Angle: 18°

h(m)	E(lx)	D(m)
1	9864	0.31
2	2466	0.62
3	1096	0.93
4	616	1.24
5	395	1.55

Luminous flux luminaire  
1637 lm


### Electrical

Frequency (Hz)	50/60
Dimmable	Yes
Driver	Integrated
Emergency	Without
Insulation class	I

### Physical

Color	Black
Orientation	Adjustable
Weight (kg)	1.90
Rotation (°)	360

### Certification / Marking




## Solid Pure Ceiling/Wall Dali Version




---

Honeycomb anti-glare screen  
08.8763.14




---

Blue filter  
08.8766.64.OD




---

Sky blue filter  
08.8766.65.OD



---

Amber filter  
08.8766.66.OD



---

Red filter  
08.8766.67.OD



---

Holding ring  
08.8768.14