

09.2893.14.DA - Black

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.


Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1772                |
| Lamp category   | LED   | Mountings      | Surface             |
| Power (W)       | 23W   | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 35        |
| Beam angle C90-270 (°) | 35        |



Luminous flux lumineuse  
1772 lm

|             |              |             |  |
|-------------|--------------|-------------|--|
| Beam Angle: | 35°          |             |  |
| <u>h(m)</u> | <u>E(lx)</u> | <u>D(m)</u> |  |
| 1           | 4534         | 0.64        |  |
| 2           | 1133         | 1.27        |  |
| 3           | 504          | 1.91        |  |
| 4           | 283          | 2.54        |  |
| 5           | 181          | 3.18        |  |

## Electrical

|                       |               |                         |   |
|-----------------------|---------------|-------------------------|---|
| <b>Frequency (Hz)</b> | 50/60         | <b>Insulation class</b> | I |
| <b>Dimmable</b>       | Yes           |                         |   |
| <b>Driver</b>         | Integrated    |                         |   |
| <b>Driver type</b>    | Dimmable DALI |                         |   |
|                       | 1             |                         |   |
| <b>Emergency</b>      | Without       |                         |   |

## Physical

|              |            |
|--------------|------------|
| Color        | Black      |
| Orientation  | Adjustable |
| Weight (kg)  | 1.90       |
| Rotation (°) | 360        |


Solid Pure Ceiling/Wall Dali Version




Holding ring  
08.8768.14



Amber filter  
08.8766.66.OD




Sky blue filter  
08.8766.65.OD



Blue filter  
08.8766.64.OD



Honeycomb anti-glare screen  
08.8763.14



Red filter  
08.8766.67.OD