


Solid Pure Ceiling/Wall Dali Version

■ 09.2896.14.DA - Black

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	2075
Lamp category	LED	Mountings	Surface
Power (W)	23W	Environment	Indoor
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	35
Beam angle C90-270 (°)	35



Beam Angle: 35°

h(m) E(lx) D(m)

1 5310 0.64

2 1327 1.27

3 590 1.91

4 332 2.54

5 212 3.18


Luminous flux luminaire
2075 lm

Electrical

Frequency (Hz)	50/60
Dimmable	Yes
Driver	Integrated
Emergency	Without
Insulation class	I

Physical

Color	Black
Orientation	Adjustable
Weight (kg)	1.90
Rotation (°)	360




Solid Pure Ceiling/Wall Dali Version




Holding ring
08.8768.14




Honeycomb anti-glare screen
08.8763.14




Blue filter
08.8766.64.OD



Sky blue filter
08.8766.65.OD



Amber filter
08.8766.66.OD



Red filter
08.8766.67.OD