

Solid Pure Ceiling/Wall Dali Version

09.2968.30.DA - White

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	4696
Lamp category	LED	Mountings	Surface
Power (W)	53W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	15
Beam angle C90-270 (°)	15



Beam Angle: 15°

h(m) E(lx) D(m)

1 31966 0.26

2 7992 0.52

3 3552 0.78

4 1998 1.05

5 1279 1.31



Luminous flux luminaire
4696 lm

Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
	1		
Emergency	Without		

Physical

Color	White
Orientation	Adjustable
Weight (kg)	1.90
Rotation (°)	360



Solid Pure Ceiling/Wall Dali Version




Holding ring
08.8768.14




Amber filter
08.8766.66.OD




Honeycomb anti-glare screen
08.8763.14



Blue filter
08.8766.64.OD



Red filter
08.8766.67.OD



Sky blue filter
08.8766.65.OD