



## Solid Pure Ceiling/Wall Dali Version

■ 09.2970.14.DA - Black

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.


Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 4609                |
| Lamp category   | LED   | Mountings      | Surface             |
| Power (W)       | 53W   | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 80    |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 45        |
| Beam angle C90-270 (°) | 45        |



Beam Angle: 45°

h(m) E(lx) D(m)

1 9417 0.82

2 2354 1.65

3 1046 2.47

4 589 3.30

5 377 4.12



Luminous flux luminaire  
4609 lm

### Electrical

|                |               |                  |   |
|----------------|---------------|------------------|---|
| Frequency (Hz) | 50/60         | Insulation class | I |
| Dimmable       | Yes           |                  |   |
| Driver         | Integrated    |                  |   |
| Driver type    | Dimmable DALI |                  |   |
|                | 1             |                  |   |
| Emergency      | Without       |                  |   |

### Physical


|              |            |
|--------------|------------|
| Color        | Black      |
| Orientation  | Adjustable |
| Weight (kg)  | 1.90       |
| Rotation (°) | 360        |



Solid Pure Ceiling/Wall Dali Version




Holding ring  
08.8768.14




Sky blue filter  
08.8766.65.OD




Honeycomb anti-glare screen  
08.8763.14



Amber filter  
08.8766.66.OD



Blue filter  
08.8766.64.OD



Red filter  
08.8766.67.OD