



Solid Pure Ceiling/Wall Dali Version

■ 09.2976.14.DA - Black

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.


Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	4892
Lamp category	LED	Mountings	Surface
Power (W)	53W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	45
Beam angle C90-270 (°)	45



Beam Angle: 45°

	h(m)	E(lx)	D(m)
1	9995	0.82	
2	2499	1.65	
3	1111	2.47	
4	625	3.30	
5	400	4.12	



Luminous flux luminaire
4892 lm

Electrical



Frequency (Hz)	50/60	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
	1		
Emergency	Without		

Physical

Color	Black
Orientation	Adjustable
Weight (kg)	1.90
Rotation (°)	360





Solid Pure Ceiling/Wall Dali Version



Blue filter
08.8766.64.OD

Red filter
08.8766.67.OD

Holding ring
08.8768.14



Sky blue filter
08.8766.65.OD

Honeycomb anti-glare screen
08.8763.14

Amber filter
08.8766.66.OD