


### Solid Pure Ceiling/Wall Dali Version

09.2982.30.DA - White

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.




#### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 3763                |
| Lamp category   | LED   | Mountings      | Surface             |
| Power (W)       | 53W   | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

#### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 45        |
| Beam angle C90-270 (°) | 45        |



Beam Angle: 45°

|   | h(m) | E(lx) | D(m) |
|---|------|-------|------|
| 1 | 7688 | 0.82  |      |
| 2 | 1922 | 1.65  |      |
| 3 | 854  | 2.47  |      |
| 4 | 481  | 3.30  |      |
| 5 | 308  | 4.12  |      |


Luminous flux luminaire  
3763 lm

#### Electrical




|                |               |                  |   |
|----------------|---------------|------------------|---|
| Frequency (Hz) | 50/60         | Insulation class | I |
| Dimmable       | Yes           |                  |   |
| Driver         | Integrated    |                  |   |
| Driver type    | Dimmable DALI |                  |   |
|                | 1             |                  |   |
| Emergency      | Without       |                  |   |

#### Physical

|              |            |
|--------------|------------|
| Color        | White      |
| Orientation  | Adjustable |
| Weight (kg)  | 1.90       |
| Rotation (°) | 360        |



Solid Pure Ceiling/Wall Dali Version



---


Red filter  
08.8766.67.OD

---

Amber filter  
08.8766.66.OD

---

Sky blue filter  
08.8766.65.OD



---

Blue filter  
08.8766.64.OD

---

Honeycomb anti-glare screen  
08.8763.14

---

Holding ring  
08.8768.14